



Impact Driver LXT®, DTD173Z

18V, 1/4", 180 Nm, 0 - 3 600 min⁻¹

Model DTD173 is a Impact Driver powered by an 18V LXT Li-Ion battery

Feature and Benefits: Slim tool body. Ring illumination LED. Light mode. Compact design with an overall length of 111 mm. Easy to see switch panel. Optimal battery layout. Assist mode



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 / 2100 / 3200 / 3600 min ⁻¹
Max Fastening Torque Impact Drill	20 / 50 / 170 / 180 Nm
Tightening Capacity Standard Bolt	M5 - M16
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Impacts per Minute (IPM)	0 - 1100 / 2600 / 3600 / 3800 min ⁻¹
Driving Shank	1/4 "
Sound Power Level (L _{WA})	108 dB(A)
Sound Pressure Level (L _{pA})	100 dB(A)

User benefits

- Electronic 4 stage impact power selection for added versatility
- Well balanced with a low center of gravity for easy operation
- Slim body design for a good grip
- Electric brake for maximum productivity and increased operator safety
- Anti wobbling bit structure

EAN 0088381779210

Link to product - www.makitauk.com



Related products

■ Standard AC

346317-0
Belt Hook



■ Other

User manual

Parts drawing