

40VMax Router XGT®, RP001GZ02

1/2"



Technical specifications

Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	8000 - 25000 min ⁻¹
Max. Collet Capacity	1/4, 3/8, 1/2 "
Plunge capacity	0 - 60 mm
AWS ready	✓
Sound Power Level (L _{WA})	100 dB(A)
Sound Pressure Level (L _{pA})	92 dB(A)
Product net weight	3,3 kg
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	4,0 - 5,2 kg
Product Dimensions (L x W x H):	135 x 275 x 288 mm
Vibration Level, Cutting Grooves in MDF	6,3 m/s ²

User benefits

- Soft start for smooth start-ups
- Anti-restart function minimises accidental start-up
- Variable speed control dial enables user to match the speed to the application for greater versatility

EAN 0197050005427

Link to product - www.makitauk.com



Related products

Standard AC

122850-4

Dust Nozzle



122G61-3

Guide Holder Assembly



1914M8-1

ACCESSORY SET

256861-8 (2x)

Rod 8



342428-9

Straight Guide



4130A9-4

Chip Deflector



821552-6

Makpac case (4)



Optional AC

122G61-3

Guide Holder Assembly



256861-8 (2x)

Rod 8



836138-3

Inner Tray RP001G



Other

User manual

Parts drawing